

SC ROLIFT SERV SRL punct de lucru Chisoda,
DN 59 km 8+130 m stanga (Calea Sagului),
Zona Industriala INCONTRO,
Registrul comerțului J35/1875/2009 codul fiscal nr. RO 26098183
RO63OTPV190000600945RO01, OTP Bank www.rolift.ro

MOTOSTIVUITOR FRONTAL DIESEL marca HELI model CPCD25 M3H

- sarcina de ridicare 2500 kg la cg 500 mm
- propulsie Diesel- motor **MITSUBISHI S4S**
- transmisie hidraulica Powe Shift 1/1
- catarg **TRIPLEX**
- inaltime de ridicare 4.800 mm
- inaltime libera : 1.155 mm
- inclinare catarg fata /spate : 3/6 grade
- 4 roti, cauciucuri solide
- 3 valve cu conexiune hidraulica
- furci 1220 mm
- translatie laterala, **Casacade**
- parbriz fata cu stergator inclus
- schimbator electric inainte-inaoi
- contor orar
- lumini lucru fata, girofar, alarma mers inapoi,
- scaun operator cu centura de siguranta
- volan reglabil
- sensor prezenta operator

Norma de poluare EURO III

Specificatiile tehnice sunt descrise in detaliu in Anexa 1


Garantie motostivuitor 24 luni sau 2.000 de ore de functionare (care intervine prima), cu contract de service.



Anexa 1

Caracteristici principale

1	Producator	HEU		
2	Model	CPCD25		
3	Tipul de combustibil	Diesel		
4	Capacitate nominala	Q	kg	2500
5	Centru de greutate	c	mm	500
6	Catarg triplex	ZSM480		
7	Inaltimea maxima de ridicare	H	mm	4800
8	Free lift	H3	mm	1155
9	Inaltime catarg retras	H3	mm	2195
<i>Dimensiuni</i>				
10	Ampatament	L1	mm	1650
11	Inaltime acoperis protectie	H4	mm	2150
12	Lungime totala (cu furci)	L1	mm	3858
13	Lungime fara furci	L'	mm	2638
14	Latime	W1	mm	1150
15	Consola	L2	mm	473
16	Garda la sol cu sarcina	H5	mm	115
17	Ecartament fata/spate	W3/W2	mm	970/970
18	Raza de intoarcere exterior	r	mm	2310
19	Coridor lucru palet (1200x800)	Ast	mm	4133
20	Raza de intoarcere interior	r'	mm	180
21	Inclinatie catarg (inainte/inapoi)	α/β	deg	6/6
22	Dimensiune furci	t/w/L3	mm	40/122/1220
<i>Performante</i>				
23	Viteza maxima de deplasare (cu/fara sarcina)			km/h 16.5/16.7
24	Viteza de ridicare (cu/fara sarcina)			mm/s 510/560
25	Viteza de coborare (cu/fara sarcina)			mm/s 450/500
26	Tractiune (cu/fara sarcina)			kN 18/15
27	Deplasare in panta (cu/fara sarcina)			% 29/23
28	Greutate			kg 3990
29	Dimensiune anvelopa fata			7.00-12-12PR
30	Dimensiune anvelopa spate			6.00-9-10PR
31	Tractiune			2x/2
32	Cauciucuri			pneumatice
<i>Motor</i>				
33	Motor	MITSUBISHI S4S		
34	Putere	Kw/rpm	35.3/2250	
35	Cuplu motor	Nm/rpr	177/1700	
36	Nr cilindri/capacitate cilindrica	pcs/L	4-94x120	
37	Capacitate rezervor	L	60	
<i>Altele</i>				
38	Frana	Hidraulica		
39	Frana de mana	Mecanica		
40	Transmisie nr. viteze Fwd/Bwd	Power shift 1/1		
41	Nr. functii hidraulice	3		



Ast: 直角堆垛通道宽度
Right angle stacking aisle width
a: 间隙 Clearance

