



SC ROLIFT SERV SRL punct de lucru Chisoda,  
DN 59 km 8+130 m stanga (Calea Sagului),  
Zona Industriala INCONTRO,  
Registrul comerțului J35/1875/2009 codul fiscal nr. RO 26098183  
RO63OTPV190000600945RO01, OTP Bank www.rolift.ro

industry - construction - agriculture

### Motostivuator marca HELI model CPD35-W2Y

- propulsie Diesel
- transmisie hidraulica power shift1/1
- sarcina de ridicare 3500 kg la cg 500 mm
- **catarg Duplex**
- inaltime de ridicare **3300** mm,
- free lift 150mm
- furci 1220 mm
- roti, pneumatice
- 3 valve cu conexiune hidraulica
- directie asistata hidraulic(servodirectie)
- frana de mana mecanica
- translatie laterala cu actionare hidraulica GC30G
- girofar, alarma mers inapoi, oglinzi
- acoperis ploaie
- parbriz fata cu stergator
- scaun cu centura siguranta
- sistem lumini faruri fata

*Specificatiile tehnice in detaliu le gasiti in anexa 1*

**Livrare din stoc in limita stocului disponibil**



Anexa 1

<i>Caracteristici principale</i>				
1	Producator	<b>HELI</b>		
2	Model	CPCD35-W2Y		
3	Tipul de combustibil	Diesel		
4	Capacitate nominala	Q	kg	3500
5	Centru de greutate	c	mm	500
6	Catarg duplex	M330		
7	Inaltimea maxima de ridicare	<b>h3</b>	mm	3300
8	Free lift	<b>h2</b>	mm	150
9	Inaltime catarg retras/ridicat	<b>h1</b>	mm	2475/4563
<i>Dimensiuni</i>				
10	Ampatament	L5	mm	1900
12	Lungime totala (cu furci)	L1	mm	4344
13	Lungime fara furci	L2	mm	3124
14	Latime fata/spate	B	mm	1160/1100
15	Consola	x	mm	644
16	Garda la sol cu sarcina fara sarcina	m1	mm	270
17	Ecartament	R/P	mm	580
18	Raza de intoarcere	Wa	mm	3315
20	Inclinatie catarg (inaine/inapoi)	<b>a/b</b>	deg	10/12
21	Dimensiune furci	t/w/L3	mm	45/125/1220
22	Tip/latime incarcare	S	mm	IIIA/1060
<i>Performante</i>				
23	Viteza maxima de deplasare (inainte/inapoi)			km/h 20/20
24	Viteza de ridicare (cu/fara sarcina)			m/s 0,50/0,55
25	Viteza de coborare (cu/fara sarcina)			m/s 0,45/0,5
26	Tractiune (cu sarcina)			kN 15.0
27	Deplasare in panta (cu/fara sarcina)			% 16
28	Greutate			kg 5300
29	Dimensiune anvelopa fata	15-19.5 TL		
30	Dimensiune anvelopa spate	10-16.5-8 PR		
31	Tractiune	2x/2		
32	Cauciucuri	pneumatice		
<i>Motor</i>				
33	Motor	ISUZU 4JG2		
34	Putere	kW/rpm		46/2450
35	Cuplu motor	kw/rpm		186.2/1600
36	Nr cilindrii/capacitate cilindrica	pcs/L		4/3.05
37	Capacitate rezervor	L		60
<i>Altele</i>				
38	Frana	Hidraulica		
39	Frana de mana	Mecanica		
40	Transmisie nr. viteze Fwd/Bwd	Power shift 1/1		
41	Nr. functii hidraulice	3		